



INTEGRAL TECHNOLOGIES


FA-ACP-0X Series Analogue Addressable Control Panel



APPROVED TO THE REQUIREMENTS OF EN54 Pt 2 & Pt 4 1999

Specifications:

Loops	1 to 4 loops in single cabinet. Expandable up to 96 loops in multiple cabinets.
Primary Supply Voltage	85~264 VAC
EMC Standard	EN55022 Class B EN61000-4-2,3,4,5,6,8,11 EN61000-3-2,3
Secondary Supply Voltage	24V DC Nominal
Power Supply Rating	65W or 150W
Quiescent Current (Without Devices)	130mA
Auxiliary Relay Ratings	50V AC / DC 1 Amp Resistive (Min 100mA, 6V)
Repeater Outputs	Open Collector 24V DC 100mA Max
Dimensions 1~4 Loops	W 340mm x H 370mm x D 125mm
IR Keypad Batteries	2 x AAA
Fuses	Battery: 3A Printer: 1A
Box *	1.5mm Aluminum Or Mild Steel Coated White
Cable Entries	Back Through Cut Out / Top By 6 Removable Plugs
Battery Capacity	Up To 2 x 12V 12Ah
Weight	4.2 Kgs



CE DECLARATION OF CONFORMITY

This Panel is CE Marked to Show that it Conforms to the Requirements of the Following European Community Directives:

- Electromagnetic Compatibility Directive 89/336/EEC (and the Amending Directive 92/31/EEC)
- Low Voltage Directive 73/23/EEC