



INTEGRAL TECHNOLOGIES

FA-ABG

Addressable Break Glass



FA-ABG-01



FA-ABG-WP

Features:

- Two Wire Connection for Easy Installation
- Compatible with Standard Single-Gang Mounting Boxes
- Suitable for Flush Mounting or Surface Mounting
- Simple DIP switch Setting
- Integral LED Controlled from Panel
- Tested to BS5839 Part 2

Description:

The FA-ABG is Designed to be Used as a Component of a Compatible Fire Control System Using Intech Analogue Addressable Devices. It is a Dedicated Addressable Break Glass Unit for Installation on a Two Wire Communication Circuit Providing Both Signaling of Alarm to the Monitoring Control Panel and Local LED Indication of Activation.

The FA-ABG may be Installed as Either a Flush or Surface Mounted Device in a Normal Internal Environment. It is not Intended for Use in an Externally Exposed or Hazardous Location.

The FA-ABG May be Flush Mounted to Compatible Electrical Boxes.

Specifications:

Minimum Operating Voltage:	15V
Maximum Operating Voltage:	32V
Standby Current:	40 uA
Alarm Current:	20 mA

Models available

FA-AGB-01	Standard (indoor)
FA-ABG-F	Standard (indoor) with FLIP cover
FA-ABG-WP	Weatherproof (outdoor)