



# INTEGRAL TECHNOLOGIES

## FA-AGD-XX Series

### Addressable GAS detector



**FA-AGD-C**



**FA-AGD-W**

#### Features:

- Model FA-AGD-X Series Detectors for Sensing and Monitoring LPG, CO and Natural Gas.
- Easy to Install in Wall or Ceiling.
- Using Microprocessor for Circuit Control and Gas Monitoring to Assure Performance Stability and Reliability.
- Sounding a Loud Alarm Signal of 85 dB at Alarm Mode.
- Simple address selection by DIP switch
- Ergonomic Design of Detector Casing.
- No Battery is Required for Circuit Control.
- Relay Output Provides Relay NO/NC (Normal Open/Normal Close) Contact for Connection with a Central Monitoring System or Other Applications (Exhaust Fans, Gas Valve Etc.).

| Model    | Mount Type |
|----------|------------|
| FA-AGD-C | Ceiling    |
| FA-AGD-W | Wall       |

#### Specifications:

|                       |                            |
|-----------------------|----------------------------|
| Power Supply          | 24V DC or 220 VAC, 50/60Hz |
| Power Consumption     | 7W                         |
| Dimensions            |                            |
| FA-AGD-C              | 120D – 51H mm              |
| FA-AGD-W              | 120H – 68W – 40D mm        |
| Operating Temperature | 0°C ~ 40°C                 |
| Sensitivity           | Less Than 15% LEL          |