



INTEGRAL TECHNOLOGIES

PA-PMU-XX Series Desk top Paging microphones

Features:

The PA-PMU-XX Paging Stations in Universal Elegant Table-Top Housing with XLR Connector and 5m Connection Cable. Noise Compensated. Gooseneck, Electret Microphone with Unidirectional Characteristics. Built-In Pre-Amplifier. Lockable or soft touch button for Paging. The Actual Status is Indicated by a LED. PA-PMU-02 includes CHIME and can be with zone selection switches on request.

Specifications:

PA-PMU-01

Operating Voltage:	3 - 24V DC
Current Consumption:	Max. 40mA
Frequency:	40Hz-18Khz
AF Output Voltage:	-38 +/- 2db / 2 K Ω
Ambient Temperature:	Max. 5...50°C
Dimensions:	110W x 15/35H x 130D mm
Gooseneck:	\varnothing 8 x 430 mm
Weight:	Approx. 600 Gms.
Color:	Black



PA-PMU-01

PA-PMU-02

Operating Voltage:	12/24V AC/DC
Current Consumption:	Max. 40mA
Frequency:	40Hz-18Khz
AF Output Voltage:	-43 +/- 2db / 2 K Ω
Ambient Temperature:	Max. 5...50°C
Dimensions:	110W x 15/35H x 130D mm
Gooseneck:	\varnothing 8 x 330 mm
Weight:	Approx. 800 Gms.
Color:	Black



PA-PMU-02